2022年10月17日 アドバンテック株式会社

IIOT 製品仕様変更のお知らせ: ULI-211CI (BB-FOSTCDRI)

平素は格別のご高配を賜り、厚く御礼申し上げます。

この度、ULI-211CI (BB-FOSTCDRI)のラベル仕様が変更になりますので、ご案内申し上げます。 なお、在庫が販売終了次第変更します。注文の方法は変更有りません。

記

- 1. Reason for the Change: Branding / UL File Change
- 2. Affected Products: ULI-211CI (BB-FOSTCDRI)

3. Impact on Application: No change to form, fit, or function.

Item	Impact
Impact on Mechanical Design	No
Impact on Software Compatibility	No
Impact on Environment Characteristics	No
Impact on System Certifications	YES – The UL file numbers are changing. Add UKCA. See
	label plate below.
Physical Outlook Change	Yes
Ordering P/N Change	No
Cut-in Implement	Component Running Change

4. Description of the Change(s):

Affected	Current	New	Category	Outlook Difference	Reason
Models	Component	Component		Old name plate	
ULI-211CI BB- FOSTCDR I	20BB250- 10538-00	1990038124T00 0	Label	Model FOSTCDRI Fiber Optic to RS-232/422/485 With Triple Isolation Switch On 1 RX Send Data TX Enable 1 RX Send Data TX Enable 2 RX Send Data TX Enable 3 2 Wire 4 Wire 4 Wire 4 Wire 4 Wire 5 Term. In Out TX Black In RDA(-)/RS-232 IN 8 77 RX Baad TDB(+) 10 192 RB Bad TDA(-)/RS-232 OUT 12 Multiple Fiber Point to-Point Down prosition is On B-B SMARTWORX Powered by ADANTECH advantech-bb.com 1 12 RS-232 RS-422/485	Branding

				New name plate	
				## 10-48 VDC ## 0-2A RS-232/422/485 to Mulit-mode Fiber Optic Converter With Triple Isolation Model FORTODRE Switch On Off To Kniele To Kni	
ULI-211CI BB- FOSTCDR I	20BB7674R 1	20BB7674R2	Label	This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any that may cause undesired operation. Ind. Cont. Eq. 44W2 E222870 LISTED Ind. Cont. Eq. For HAZ LOC 3HTV E245458 Class 1, Div.2, Groups A. B. C. D Temp. Code: T4A Max. Input Power: 1.75W WARNING - Explosion Hazard - Do Not Disconnect While Circuit Is Live Unless Area is Known To Be Non-Hazardous. New Name Plate This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any that may cause undesired operation. CULUS Ind. Cont. Eq. For HAZ LOC 5DX5 E327848 LISTED Ind. Cont. Eq. For HAZ LOC 5DX5 E327848 Under Cont. Eq. For HAZ LOC 5DX5 E327848 Ind. Cont. Eq. For HAZ LOC 5DX5 E337172 Class 1, Div.2, Groups A, B, C, D Temp. Code: T4A Max. Ambient Temp: 80C Max. Input Power: 1.75W Factory ID: USH3 WARNING - Explosion Hazard - Do Not Disconnect While Circuit Is Live Unless Area is Known To Be Non-Hazardous.	Complianc



アドバンテック株式会社マーケティング部

〒111-0032東京都台東区浅草6-16-3

E-mail: ajp_callcenter@advantech.com

TEL: 0800-500-1055 (フリーダイヤル) FAX: :03-6802-1022

以上